

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2021/0125719 A1 Peret et al.

Apr. 29, 2021 (43) **Pub. Date:**

(54) SYSTEM, METHOD, AND APPARATUS FOR MONITORING, REGULATING, OR CONTROLLING FLUID FLOW

(71) Applicant: **DEKA Products Limited Partnership**,

Manchester, NH (US)

(72) Inventors: Bob D. Peret, Bedford, NH (US);

Brian H. Yoo, Arlington, MA (US); Derek G. Kane, Manchester, NH (US); Dean Kamen, Bedford, NH (US); Colin H. Murphy, Cambridge, MA (US); John M. Kerwin, Manchester,

NH (US)

(21) Appl. No.: 17/139,195

(22) Filed: Dec. 31, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/248,200, filed on Aug. 26, 2016, now Pat. No. 10,894,638, which is a continuation of application No. 14/213,373, filed on Mar. 14, 2014, now Pat. No. 9,435,455, which is a continuation-in-part of application No. 13/834,030, filed on Mar. 15, 2013, now Pat. No. 9,372,486, which is a continuation-in-part of application No. 13/333,574, filed on Dec. 21, 2011, now Pat. No. 10,453,157, which is a continuation-in-part of application No. PCT/US11/66588, filed on Dec. 21, 2011, which is a continuation-in-part of application No. 13/723,238, filed on Dec. 21, 2012, now Pat. No. 9,759,369, which is a continuation-in-part of application No. 13/333,574, filed on Dec. 21, 2011, now Pat. No. 10,453,157, which is a continuation-in-part of application No. PCT/US11/66588, filed on Dec. 21, 2011, said application No. 13/834,030 is a (Continued)

Publication Classification

(51) Int. Cl. G16H 40/67 (2006.01)F16K 31/02 (2006.01)

A61M 5/14	(2006.01)
A61M 39/28	(2006.01)
A61M 5/168	(2006.01)
G05D 7/06	(2006.01)
F16M 11/04	(2006.01)
F16M 13/00	(2006.01)
F16M 13/02	(2006.01)
A61M 5/142	(2006.01)
A61M 5/172	(2006.01)
F16K 7/06	(2006.01)
G16H 40/40	(2006.01)
G16H 20/17	(2006.01)
F16K 1/00	(2006.01)
B65D 47/20	(2006.01)
F16K 7/04	(2006.01)
G01F 11/30	(2006.01)
	` ′

(52) U.S. Cl.

CPC G16H 40/67 (2018.01); A61M 39/284 (2013.01); A61M 5/14 (2013.01); A61M **39/281** (2013.01); **A61M 5/16877** (2013.01); G05D 7/0635 (2013.01); F16M 11/041 (2013.01); F16M 13/00 (2013.01); F16M 13/022 (2013.01); A61M 5/1411 (2013.01); A61M 5/14212 (2013.01); A61M 5/16804 (2013.01); A61M 5/16881 (2013.01); A61M 5/172 (2013.01); F16K 7/06 (2013.01); G16H 40/40 (2018.01); G16H 20/17 (2018.01); F16K 1/00 (2013.01); B65D 47/2018 (2013.01); F16K 7/04 (2013.01); G01F 11/30 (2013.01); Y10T 137/7287 (2015.04); A61M 2005/14208 (2013.01); A61M 2205/3306 (2013.01); A61M 2205/3576 (2013.01); A61M 2205/50 (2013.01); A61M 2205/502 (2013.01); F16K 31/02 (2013.01)

ABSTRACT

An apparatus, system and method for regulating fluid flow are disclosed. The apparatus includes a flow rate sensor and a valve. The flow rate sensor uses images to estimate flow through a drip chamber and then controls the valve based on the estimated flow rate. The valve comprises a rigid housing disposed around the tube in which fluid flow is being controlled. Increasing the pressure in the housing controls the size of the lumen within the tube by deforming the tube, therefore controlling flow through the tube.

